



P2 Reference

Pin	Signal
1	ICS H/P Lo
2	ICS Mic Hi
3	ICS H/P Left Hi
4	ICS Mic Lo

Item	p.n.	Qty.	unit	Description
12	30200	0.2	mL	Adhesive
11	60079	1	ea	Label Intercom Harness, FPD, Type 2
10	60049	1	ea	Label overlaminating, 125 x 3
9	30034	1.5	in	1/8" heat shrink tubing
8	30025	1	ea	Grommet 1/8"
7	85458	1	ea	Enclosure, machined
6	30024	2	ea	Grommet 3/16"
5	40235	1	ea	Cordset, 5 DIN Jack
4	40013	1	ea	Cordset, 5 DIN Plug
3	40119	4	ea	Terminal, male, micro-fit, 20-24 AWG
2	40132	1	ea	Plug, Micro-fit, 4 circuit
1	90024	4	in	Cable, 4 conductor, 22 AWG, gray

THIS DRAWING IS THE PROPERTY OF THE KENNEDY TECHNOLOGY GROUP, ROSE HILL, KANSAS

<h1>Kennedy Technology</h1>		UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES LINEAR Fractional - 1/32" 0.0 ± 0.15 0.00 ± 0.015 0.000 ± 0.0015 ANGULAR ± 0.5 DEG.	
REFERENCE 95205	Intercom Harness Assy, FPD, Type 2		
SIZE B	CADFILE	DWG NO. 85538	REV NO. 1
SCALE: NONE		EFFECTIVE sn:	
SHEET 1 OF 1		FOR ASSISTANCE CONTACT: vox 316-776.1111 fax 316-776.9035	CHECKED _____ DATE _____ DESIGN _____ DATE _____