

A B C D E F G H J K L M N P

1

2

3

4

5

6

7

8

9

Align
+/- 1/2"

16-heat shrink over the braid-1"

J1

white

red-cut off

KTG Inc

18, 19

12

11

Put glue on web
before heat shrink

13

10

5.0"

P1

1

2.0"

5

P2

NOTE ORIENTATION AND RELATIVE POSITION OF PLUGS

20	30037	0	1	in	3/32" heat shrink
19	85925	0	1	ea	label, s/n - p/n
18	60049	0	1	ea	label, laminating
17	30034	0	1	in	1/8" heat shrink
16	30049	0	1	in	1/16" heat shrink
15	90132	0	4	in	Wire, 22 gage, red, 300V
14	90130	0	4	in	Wire, 22 gage, blk, 300V
13	30200	0	0.2	mL	Adhesive
12	30502	0	1	ea	Tie wrap, 4", black
11	30070	0	63	in	Sleeve, polyester, 1/4", black, non-fray
10	30071	0	1.5	in	Tubing, heat shrink, 5/16"
9	40025	0	2	ea	Contact, pin, 24-30 ga
8	40015	0	1	ea	Plug, 2-conductor
7	75040	0	1	ea	Fuse, 1A
6	75036	0	1	ea	Holder, fuse, 3AG
5	85462	0	1	ea	Cordset, black, RJ11
4	40153	0	1	ea	Terminal, female, Micro-fit, gold, 26-30 AWG
3	40118	0	1	ea	Terminal, female, Micro-fit, gold, 20-24 AWG
2	40115	0	1	ea	Receptacle, Micro-fit, 2 circuit
1	40127	0	1	ea	Cordset, plug, 3.5mm, stereo, Rt. angle, 72"
Item	p.n.	Rev	Qty.	unit	Description

Sleeve to cover power splice

6,7

red

15

red

14

P3

8

20-1/2" typ.2

splice

red

fuse

green

black

red

P3

P2

THIS DRAWING IS THE PROPERTY OF THE KENNEDY TECHNOLOGY GROUP, ROSE HILL, KANSAS

Kennedy Technology

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES
LINEAR
Fractional - 1/32"
0.0 ≤ ± 0.15
0.00 ≤ ± 0.015
0.000 ≤ ± 0.0015
ANGULAR
±0.5 DEG.

REFERENCE XXXXXX		Harness, Valentine		EFFECTIVE sn:	
SIZE B	CADFILE	DWG NO. 95209	REV NO. 0	DATE	
SCALE: NONE		FOR ASSISTANCE CONTACT: vox 316-776-1111 fax 316-776-9035		DRAWN	DATE
SHEET 1 OF 1				CHECKED	DATE

A B C D E F G H J K L M N P