

1
2
3
4
5
6
7
8
9

A B C D E F G H J K L M N P

Align
+/- 1/2"

16-heat shrink over the braid-1"

KTG Inc

Put glue on web
before heat shrink

2.0"

Sleeve to cover power splice

red

splice

20-1/2" typ.2

red

green

black

red

white

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18, 19

J1

P1

P2

P3

Rev	Description	by	Date
0	Release	jj	10/5/05

20	30037	0	1	in	3/32" heat shrink
19	60135	0	1	ea	label, device harness
18	60049	0	1	ea	label, laminating
17	30034	0	1	in	1/8" heat shrink
16	30049	0	1	in	1/16" heat shrink
15	90132	0	4	in	Wire, 22 gage, red, 300V
14	90130	0	4	in	Wire, 22 gage, blk, 300V
13	30200	0	0.2	mL	Adhesive
12	30502	0	1	ea	Tie wrap, 4", black
11	30070	0	63	in	Sleeve, polyester, 1/4", black, non-fray
10	30071	0	1.5	in	Tubing, heat shrink, 5/16"
9	40025	0	2	ea	Contact, pin, 24-30 ga
8	40015	0	1	ea	Plug, 2-conductor
7	75040	0	1	ea	Fuse, 1A
6	75036	0	1	ea	Holder, fuse, 3AG
5	85462	0	1	ea	Cordset, black, RJ11
4	40153	0	1	ea	Terminal, female, Micro-fit, gold, 26-30 AWG
3	40118	0	1	ea	Terminal, female, Micro-fit, gold, 20-24 AWG
2	40115	0	1	ea	Receptacle, Micro-fit, 2 circuit
1	40049	0	1	ea	Cordset, plug, 2.5mm, mono, straight, 72"
Item	p.n.	Rev	Qty.	unit	Description

THIS DRAWING IS THE PROPERTY OF THE KENNEDY TECHNOLOGY GROUP, ROSE HILL, KANSAS					
Kennedy Technology				UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES LINEAR Fractional - 1/32" 0.0 ± 0.15 0.00 ± 0.015 0.000 ± 0.0015 ANGULAR ±0.5 DEG.	
REFERENCE 95209	Harness, Valentine				
SIZE B	CADFILE	DWG NO. 95372	REV NO. 0	EFFECTIVE sn:	
SCALE: NONE			FOR ASSISTANCE CONTACT: vox 316-776-1111 fax 316-776-9035		DATE
SHEET 1 OF 1			CHECKED		DATE